

## Durham Research Online

---

### Deposited in DRO:

15 November 2019

### Version of attached file:

Accepted Version

### Peer-review status of attached file:

Peer-reviewed

### Citation for published item:

Cockell, Charles S. and Holt, John and Campbell, Jim and Groseman, Harrison and Josset, Jean-Luc and Bontognali, Tomaso R. R. and Phelps, Audra and Hakobyan, Lilit and Kuretn, Libby and Beattie, Annalea and Blank, Jen and Bonaccorsi, Rosalba and McKay, Christopher and Shrivastava, Anushree and Stoker, Carol and Willson, David and McLaughlin, Scott and Payler, Sam and Stevens, Adam and Wadsworth, Jennifer and Bessone, Loredana and Maurer, Matthias and Sauro, Francesco and Martin-Torres, Javier and Zorzano, Maria-Paz and Bhardwaj, Anshuman and Soria-Salinas, Alvaro and Mathanlal, Thasshwin and Nazarious, Miracle Israel and Ramachandran, Abhilash Vakkada and Vaishampayan, Parag and Guan, Lisa and Perl, Scott M. and Telling, Jon and Boothroyd, Ian M. and Tyson, Ollie and Realff, James and Rowbottom, Joseph and Lauernt, Boris and Gunn, Matt and Shah, Shaily and Singh, Srijan and Paling, Sean and Edwards, Tom and Yeoman, Louise and Meehan, Emma and Toth, Christopher and Scovell, Paul and Suckling, Barbara (2019) 'Subsurface scientific exploration of extraterrestrial environments (MINAR 5) : analogue science, technology and education in the Boulby Mine, UK.', *International journal of astrobiology.*, 18 (2). pp. 157-182.

### Further information on publisher's website:

<https://doi.org/10.1017/S1473550418000186>

### Publisher's copyright statement:

This article has been published in a revised form in *International Journal of Astrobiology*  
<https://doi.org/10.1017/S1473550418000186>. This version is published under a Creative Commons CC-BY-NC-ND. No commercial re-distribution or re-use allowed. Derivative works cannot be distributed. © Cambridge University Press.

### Additional information:

### Use policy

---

The full-text may be used and/or reproduced, and given to third parties in any format or medium, without prior permission or charge, for personal research or study, educational, or not-for-profit purposes provided that:

- a full bibliographic reference is made to the original source
- a [link](#) is made to the metadata record in DRO
- the full-text is not changed in any way

The full-text must not be sold in any format or medium without the formal permission of the copyright holders.

Please consult the [full DRO policy](#) for further details.

# Subsurface Scientific Exploration of Extraterrestrial Environments (MINAR 5): Analog Science, Technology, and Education in the Boulby Mine, UK

Charles S Cockell<sup>1</sup>, John Holt<sup>2</sup>, Jim Campbell<sup>2</sup>, Harrison Groseman<sup>2</sup>, Jean-Luc Josset<sup>3</sup>, Tomaso R.R. Bontognali<sup>4</sup>, Audra Phelps<sup>5</sup>, Lilit Hakobyan<sup>5</sup>, Libby Kuretn<sup>5</sup>, Annalea Beattie<sup>6</sup>, Jen Blank<sup>7</sup>, Rosalba Bonaccorsi<sup>7,8</sup>, Christopher McKay<sup>7</sup>, Anushree Shirvastava<sup>7</sup>, Carol Stoker<sup>7</sup>, David Willson<sup>7</sup>, Scott McLaughlin<sup>1</sup>, Sam Payler<sup>1</sup>, Adam Stevens<sup>1</sup>, Jennifer Wadsworth<sup>1</sup>, Loredana Bessone<sup>9</sup>, Matthias Maurer<sup>9</sup>, Francesco Sauro<sup>10</sup>, Javier Martin-Torres<sup>11</sup>, Maria-Paz Zorzano<sup>11,12</sup>, Anshuman Bhardwaj<sup>11</sup>, Alvaro Soria-Salinas<sup>11</sup>, Thasshwin Mathanlal<sup>11</sup>, Miracle Israel Nazarious<sup>11</sup>, Abhilash Vakkada Ramachandran<sup>11</sup>, Parag Vaishampayan<sup>13</sup>, Lisa Guan<sup>13</sup>, Scott M. Perl<sup>14,15,16</sup>, Jon Telling<sup>17</sup>, Ian M Boothroyd<sup>18</sup>, Ollie Tyson<sup>17</sup>, James Realff<sup>17</sup>, Joseph Rowbottom<sup>17</sup>, Boris Lauernt<sup>19</sup>, Matt Gunn<sup>19</sup>, Shaily Shah<sup>20</sup>, Srijan Singh<sup>20</sup>, Sean Paling<sup>21</sup>, Tom Edwards<sup>21</sup>, Louise Yeoman<sup>21</sup>, Emma Meehan<sup>21</sup>, Christopher Toth<sup>21</sup>, Barbara Suckling<sup>21</sup>

<sup>1</sup>UK Centre for Astrobiology, SUPA, School of Physics and Astronomy, University of Edinburgh, UK

<sup>2</sup>University of Leicester, Leicester, UK

<sup>3</sup>Space Exploration Institute, Neuchatel, Switzerland

<sup>4</sup>ETH Zurich, Department of Earth Sciences, Zurich, Switzerland

<sup>5</sup>Spaceward Bound, NASA Ames Research Center, California, USA

<sup>6</sup>MIT University, Melbourne, Australia

<sup>7</sup>NASA Ames Research Center, California, USA

<sup>8</sup>SETI Institute's Carl Sagan Center, California, USA

<sup>9</sup>European Astronaut Center, European Space Agency, Cologne, Germany

<sup>10</sup>University of Bologna, Italy

<sup>11</sup>Luleå University of Technology, Luleå, Sweden

<sup>12</sup>Centro de Astrobiología (CSIC-INTA), Torrejon de Ardoz, 28850 Madrid, Spain

<sup>13</sup>Biotechnology and Planetary Protection Group, NASA Jet Propulsion Laboratory, California Institute of Technology, USA

<sup>14</sup>California Institute of Technology / NASA Jet Propulsion Laboratory, Pasadena, California, USA

<sup>15</sup>Department of Earth Sciences, University of Southern California, Los Angeles, California, USA

<sup>16</sup>Mineral Sciences, Los Angeles Natural History Museum, USA

<sup>17</sup>School of Natural and Environmental Sciences, Newcastle University, UK

<sup>18</sup>Department of Earth Sciences, Durham University, UK

<sup>19</sup>University of Aberystwyth, UK

<sup>20</sup>Kalam Center, New Delhi, India

<sup>21</sup>Boulby Underground Laboratory, Boulby, UK

The deep subsurface of other planetary bodies is of special interest for robotic and human exploration. The subsurface provides access to planetary interior processes, thus yielding insights into planetary formation and evolution. On Mars, the subsurface might harbour the most habitable conditions. In the context of human exploration, the subsurface can provide refugia for habitation from extreme surface conditions. We describe the fifth Mine Analogue Research (MINAR 5) program at one kilometre depth in the Boulby Mine, UK in collaboration with Spaceward Bound NASA and the Kalam Centre, India, to test instruments and methods for the robotic and human exploration of deep environments on the Moon and Mars. The geological context in Permian evaporites provides an analogue to evaporitic materials on other planetary bodies such as Mars. A wide range of sample acquisition instruments (NASA drills, SPLIT robotic hammer, universal sampling bags), analytical instruments (Raman spectroscopy, Close-Up Imager, Minion DNA sequencing technology, methane stable isotope analysis, biomolecule and metabolic life detection instruments) and environmental monitoring equipment (passive air particle sampler, particle detectors and environmental monitoring equipment) was deployed in an integrated campaign. Investigations included studying the geochemical signatures of chloride and sulfate evaporitic minerals, testing methods for life detection and planetary protection around human-tended operations, and investigations on the radiation environment of the deep subsurface. The MINAR analog activity occurs in an active mine, showing how the development of space exploration technology can be used to contribute to addressing immediate Earth-based challenges. During the campaign, in collaboration with ESA, MINAR was used for astronaut familiarisation with future exploration tools and techniques. The campaign was used to develop primary and secondary school and primary to secondary transition curriculum materials on-site during the campaign which was focused on a classroom EVA simulation.

*Keywords:* analog research, Mars, subsurface, astrobiology, technology

## Introduction

The exploration of the deep subsurface of other planetary bodies is motivated by potentially high scientific returns. Particularly on bodies such as the Moon or Mars, where impact gardening has disrupted and perturbed surface environments, the deep subsurface can provide access to relatively unaltered materials. On Mars, the deep subsurface is recognised to be a location that may have hosted habitable conditions in its past and has a high possibility of hosting such conditions today (Boston *et al.* 1992; Hofmann 2008). For example, these locations have the potential to provide access to materials influenced by groundwater via upwelling events. As observed on Mars in regions such as the Burns Formation, groundwater had the ability to move through permeable sediment rock pathways to record ancient water-rock and water-mineral interactions (McLennan *et al.* 2005; Clark *et al.*, 2005; Andrews-Hanna *et al.* 2010). Should these features have been host to organics or biogenic features in early Martian history when the climate was more hospitable (Ehlmann *et al.* 2011) and Earth-like, it would simultaneously provide protection and preservation of targets of astrobiological interest for future missions. Thus, the subsurface of Mars is a promising location to test the hypothesis of past life on Mars and the existence and persistence of habitable conditions on that planet.

In terms of human exploration, subsurface environments provide potential refugia from harsh surface conditions including Solar Particle Events (SPEs) and micrometeorite impacts. Although a permanent troglodyte existence may be unappealing to denizens of the Earth, in extraterrestrial environments such locations provide safe havens on the Moon, Mars, and even asteroids, particularly if deep caverns are used that have already been formed by natural processes.

Access to the subsurface of other planetary bodies can be achieved by investigating naturally uplifted crater materials (Michalski and Niles 2010), indirectly through radar

sounding (Picardi *et al.* 2005; Watters *et al.* 2006), or by drilling in robotic and human missions (Smith and McKay 2005). However, it is now understood that natural access to the subsurface is also provided by features such as volcanic and impact-produced caves and lava tubes (e.g. Cushing *et al.* 2007; Williams *et al.* 2010). These features provide compelling locations for robotic and human exploration and eventually for future human habitation.

Using deep subsurface environments on the Earth to carry out analog research is rare primarily because access to subsurface environments is often logistically difficult. Existing examples are the European Space Agency's CAVES and PANGAEA programs. In this paper, we describe the use of a deep subsurface astrobiology facility (Cockell *et al.* 2013; Payler *et al.* 2016) and Mars Yard to test instruments, develop protocols and simulate deep subsurface exploration as part of a Mine Analog Research Program (MINAR). This program takes advantage of a subsurface laboratory at the active Boulby Mine, UK and allows for technology transfer work between planetary sciences and mining (Bowler *et al.* 2013). The geological and scientific context of the underground analog activity is the presence of ~0.25 Ga-old deep subsurface evaporite deposits that contain within them chloride and sulfate salts that provide geological, geochemical, and habitability analogs for the study of salt-rich environments on other planetary bodies.

## **Methods**

### *General location of MINAR*

The Boulby Mine (run by Israel Chemicals Limited [ICL]) exploits the Zechstein evaporite deposits, the remnants of a ~250 million year old inland Permian sea that once stretched from the shoreline of the modern UK to Eastern Europe. The mine is situated in north Yorkshire, UK (Fig. 1) (Woods, 1979).

[Figure 1 here]

The Zechstein sequence contains a number of repeating evaporite mineral horizons, including chloride and sulphate salts such as halite (NaCl), sylvite (KCl), sylvinite (a mixture of NaCl and KCl), and polyhalite ( $\text{K}_2\text{Ca}_2\text{Mg}(\text{SO}_4)_4 \cdot 2\text{H}_2\text{O}$ ) that often contain impurities of other minerals and clays.

Large-scale evaporite deposits, such as those found at Boulby, provide a terrestrial analog for parts of the Martian surface and potentially deep subsurface. Chloride and sulphate minerals have been detected over much of Mars' surface and in Martian meteorites (Bridges and Grady 1999, 2000; Squyres *et al.* 2004; Langevin *et al.* 2005; Osterloo *et al.* 2008, 2010; Hynek *et al.* 2015). Brine fluids are hypothesized to exist in the shallow subsurface, and even surface regions, of present-day Mars (Zorzano *et al.* 2009; Martínez & Renno 2013; Martin-Torres *et al.* 2015, Ojha *et al.* 2015). Such saline environments can record ancient fluvial activity as well as transitions between wet and dry environmental settings. Such transitions are observed for the late Noachian-early Hesperian on Mars.

Other planetary bodies, such as the asteroid Ceres, also host salt deposits (De Sanctis *et al.* 2016; Stein *et al.* 2017) and may be locations for future robotic and human exploration. Boulby is one potential analog for the eventual robotic and human exploration of these environments.

The Boulby Mine hosts the Boulby Underground Science Laboratory which since 2005 has led research into Dark Matter and other experiments requiring low background radiation (Bettini 2011; Smith 2012; Murphy and Paling 2012; De Angelis 2017). In 2011, we assembled an underground laboratory to carry out astrobiology and space exploration research (Cockell *et al.* 2013). Building on the potentially fruitful collaboration between planetary scientists and an active mine, we established the MINE Analog Research (MINAR) program to enhance the

testing and development of instruments and scientific studies related to the robotic and human exploration of the deep subsurface (Bowler *et al.* 2013; Payler *et al.* 2016).

A question with any analog site is what advantage is to be gained in using such a site. In the case of MINAR, there are three rationales for the use of the site: 1) The investigation of life in the deep subsurface. Evaporites of different kinds are thought to underlie a substantial fraction of the Earth's continental surface area, thus the study of these environments is of scientific interest for understanding the extent of the deep biosphere and its influence on global biogeochemical cycles, 2) Test technology relevant to the subsurface exploration of other planetary bodies such as the Moon and Mars in a controlled subsurface environment with access to power, internet, wet laboratory facilities and other logistics facilities, 3) Carry out technology testing in a commercial setting (an active mine) thus enhancing technology transfer between the space and mining sectors and stimulating activity that links a planetary analog campaign to Earth-based applications.

The first MINAR event, MINAR 1, was a workshop, 'From Outer Space to Mining' held April 22-24, 2013 to define analog research in the deep subsurface and identify scientific and technical priorities for this type of research (the meeting was summarised by Bowler *et al.*, 2013). MINAR 2 (March 30-April 4, 2014) and MINAR 3 (November 17-19, 2014) were two events used to carry out analog research using planetary instrumentation. The summary of the MINAR 1 to 3 events can be found in Payler *et al.* (2016). MINAR 4 occurred from July 18-20, 2016 and was focused on the study of biosignatures in Permian evaporite polygonal formations. MINAR 5 (October 8-20, 2017), the largest of the MINAR campaigns, was carried out as a collaboration with Spaceward Bound NASA and the Kalam Centre, India and is the subject of this paper.

#### *Location of MINAR 5*

During MINAR 5, several sites were used:

- a) The Mars Yard. This was used for instrument testing and deployment of environmental monitoring equipment. Eight defined samples of the three major evaporite types in Boulby: halite (NaCl), potash (KCl), and 'polyhalite' ( $\text{K}_2\text{Ca}_2\text{Mg}(\text{SO}_4)_4 \cdot 2\text{H}_2\text{O}$ ) were procured of known geological provenance and deposited in the Mars Yard for instrument teams to use.
- b) Two excursions were implemented to well-defined polygonal features (Fig. 2). These are features in the halite formed in the original Zechstein deposit and today are found as dark black/brown lineations in the salt. The features are the location of enhanced mineral and carbon accumulations. They were used to test drilling and 3D mapping technology and to collect samples for CLUPI, UV fluorescence spectroscopy, Raman spectroscopy, and ATP/LAL analysis.
- c) Two excursions were implemented to a large halite brine seep/pool caused by water infiltration into the mine and its ponding in a mine stub. This pond is characterised by both saturated salt solutions and secondary halite precipitation around its edges. This site was used to collect samples for CLUPI, UV fluorescence spectroscopy, Raman spectroscopy, and ATP/LAL analysis.

In addition, samples were collected around the mine in regions of high human activity by NASA JPL personnel to study microbial bioload as part of a study of microbial populations in cleanroom/spacecraft facilities and to test portable real-time DNA sequencing technology.

[Figure 2 here]

#### *A Deep Subsurface Mars simulation facility*

To achieve the objectives of MINAR 5, a 'Mars Yard' was constructed adjacent to the Boulby Underground Laboratory (Fig. 1 and 2). The Mars Yard is a 720 m<sup>2</sup> space equipped with a



small internet-linked, air conditioned laboratory (2.5 x 7 m (width) x 2.3 m (height)) at one end which acts an interface to the main laboratory and the surface as well as a location to test and ready instruments for deployment. The Mars Yard area is an open area of Permian halite with large lumps of different evaporite minerals collected from different areas of the mine and brought to the Mars Yard for instrument teams to study. This was the first purpose-built planetary simulation environment to be constructed in the deep subsurface.

### *MINAR Analog Objectives*

The MINAR 5 (October 8-22, 2017) campaign had an overarching aim to test instruments and methods for the subsurface exploration of the Moon and Mars in an integrated campaign using the study of habitability and deep subsurface life as the motivator, and to use this work to develop new educational materials to advance planetary sciences in primary and secondary schools. Within this aim, the campaigns had four primary objectives:

- a) Testing of planetary exploration technology whilst studying deep subsurface life and biosignatures.* Carry out testing of planetary instrumentation for deep subsurface exploration in an integrated way from sample collection through to analysis whilst studying Permian evaporite deposits and present-day habitats, In particular, study extant life and ancient biosignatures.
- b) Astronaut operations.* During MINAR 5, the campaign was joined by ESA astronaut Matthias Maurer as part of his activities in the context of the European Space Agency (ESA) analogue training and testing programmes CAVES and PANGAEA. The purpose of attendance was to learn about planetary instrumentation proposed for Mars missions and to gain experience in a deep subsurface environment that complements lava tubes and natural fieldsite analogues used in ESA CAVES and PANGAEA, but also other artificial analogues like the future ESA LUNA facility.

c) *Education*. MINAR 5 aimed to develop new curriculum materials. During the MINAR event, the education team (Audra Phelps (lead), Lilit Hakobyan, Libby Kuretn, Annalea Beattie, Anushree Shirvastava) joined expedition team members in the deployment and testing of the equipment described in this paper. Members of the education team joined the MINAR scientists in excursions to the polygon features, brine seeps, and activities in the Mars Yard with the intention of learning about the different methods and how field work could be integrated into a classroom EVA activity. At other times, the team met in the underground laboratory to discuss and put together lesson plans that incorporated the MINAR work.

d) *Outreach*. MINAR 5 was used to reach a general audience to provide education in planetary science and astrobiology. During MINAR 5, three one-hour live links were conducted from the mine. These consisted of a format of ~ 5 minutes introduction, a ~20 minute guided tour of the Mars Yard and some of the instruments being tested, a ~15 minute guided tour of the main underground laboratory, and a ~15 minute session answering questions. These live links were carried out on October 16 (10:00 GMT) and October 18 (10:00 GMT and 15:00 GMT). They were conducted in collaboration with the Dr. A.P.J. Abdul Kalam Centre, New Delhi, India with Srijan Singh and Shaily Shah from the Kalam Centre on site at Boulby. Over 500 schools and colleges associated with the Centre took part and the live feeds were available to the over 400,000 students of the Dr APJ Abdul Kalam Technical University. The Kalam Centre aims to promote innovations, especially in governance and social enterprises, improve youth participation in national and international development and improve access to education and knowledge in all strata of Indian society. By coordinating the live links directly with the Kalam Centre, students from across India were able to learn about planetary exploration and take part in question and answer sessions about space

exploration and specifically science being carried out in Boulby as part of MINAR 5. The second set of live links involved ESA astronaut Matthias Maurer who described his reasons for being at MINAR and some of his objectives there. Throughout MINAR 5, other short (~5-10 min) live interviews were carried out with scientists involved in MINAR to explain their science and technology activities to a wider audience.

### *Instruments tested during MINAR*

During MINAR, a range of instruments was tested broadly split into sample acquisition, analysis, and environmental monitoring. In the context of Boulby, the application of these instruments was particularly focused on testing their efficacy when applied to the study of ancient evaporite minerals.

In order to emulate the type of study that might be undertaken by robotic or human explorers, samples were acquired using different methods (manual collection, SPLIT, and drilling) from the sites described in ‘Location of MINAR 5’, first analysed by non-destructive methods and they were then analysed by destructive methods (Fig. 3.) Many of these samples were taken after MINAR to be analysed in more detail by respective science teams. Here we describe representative analyses carried out in situ using the scheme shown in Fig. 3.

[Figure 3 here]

### *Sample acquisition*

Sample acquisition instrumentation was a suite of instruments designed to acquire samples more effectively, with greater cleanliness or to improve the quality of samples that can be used for further analysis (Fig. 4).

[Figure 4 here]

#### NASA Drill (NASA Ames Research Center)

MINAR 5 was used as an analogue field site validation test of drilling capabilities into ancient salt (halite) deposits and a test of contamination prevention protocols for planetary drilling.

A drill and 3 drill strings (Fig. 4) were used in Boulby mine to get up to ~0.4 meter deep samples within and along the boundaries of polygonal structures in halite at the polygons experimental area (Fig. 2).

Drilling took place with a hand-held Hilti TE 02 drill equipped with three drill strings: A 42 cm core sample string, a 40.6 cm cuttings string, and a 92.7 cm cuttings string. The longest string was a prototype string for the proposed IceBreaker Mars life detection mission (McKay *et al.* 2013). The Cuttings strings produced 1 – 5 mm-sized cuttings, while the Core string mostly recovered larger fragments (~ 0.5 cm-diameter) and several 5 cm-diameter, 1-2 cm-thick pieces (cookies) sandwiched in a 7 cm core.

An essential part of the drilling process was to ensure sterility and cleanliness of the drill string in relation to studies of biomarkers. The protocols for drill string cleaning included a combination of chemical disinfectants, flame sterilization followed by bio-burden monitoring (Hygiena UltraSnap surface swabs) using ATP luminometry to detect traces of ATP biomarker.

As flame sterilization was not possible in Boulby on account of safety procedures, previous protocols (i.e. Miller *et al.* 2008; Bonaccorsi and Stoker 2008) were modified to use only chemical disinfectants to sterilize the core string. To mitigate the lack of flame sterilization, implying the potential for high contamination, we used only the core drill bit to ensure the acquisition of a larger volume of polygon material. This way an uncontaminated sample suited for low levels of biomarkers could be obtained from the central part of the core, which is not in contact with potentially contaminated surfaces of the core string metal. Use of

cuttings was avoided to minimise use of contaminated drilled powder-sized cuttings in contact with the string thread's surface. Fine-grained cuttings have a large collective surface, enabling contamination when drilled with a potentially contaminated string thread. Furthermore, the heat generated during the drilling itself, which might influence biomarkers in the fine-grained cuttings, was mitigated by using the larger core string.

#### SPLIT (Small Planetary Impulse Tool) (University of Leicester)

A major problem facing remote robotic in situ planetary missions is ambiguity caused by the nature and characteristics of a rock's measurement surface, which may mask an underlying, more representative mineralogy, petrology or hidden biosignatures. Based on the practice of field geology, it has been firmly established for planetary surface exploration, both manned and remote, that effective sampling of rocks is key to maximizing scientific return and the delivery of mission objectives. SPLIT is a novel geotechnics approach to this problem, an instrument that breaks a rock target exactly as a field geologist would with a hammer to expose a deep internal pristine surface.

The SPLIT tip is pre-loaded by approximately 10N with the tip remaining in contact with the rock; some compliance in the system is provided by the forward bellows. The mechanism of SPLIT is actuated with a Maxon EC22 motor such that for each output rotation of the planetary gearbox, the hammer mechanism generates a single impulse. As the follower progresses the cam track, the cam body, with hammer, is displaced, thereby compressing the machined spring and storing potential energy. On completion of the cam track, the follower falls back to its original position; the compressed spring is released and thus, an impact is delivered by the hammer on the anvil, which couples the high energy impulse to the tip. This repeated impact energy is used to induce brittle fracture at the interface. However, rock materials are generally discontinuous at microscopic scales such that the crystal structure, grain

boundaries, cleavage planes, as well as micro fractures and pores, all act as matrix defects exhibiting stress concentrations. SPLIT takes advantage of this feature in the various lithologies expected in planetary exploration where the cumulative effect of the technique is intended to induce low-cycle fatigue through the accumulation of plastic deformations in the rock matrix.

Complementary to other tools, SPLIT facilitates subsequent targeted sampling and extends sampling depth of current technologies. The technique can take advantage of an irregular surface, further extending the target range of other sampling tools. Furthermore, SPLIT is a controlled technique exposing a rock interior within a few minutes and may be used to manage wear of other tool tips and thus rover energy resources or deployed as a geological ‘triage’ tool to determine rock hardness with its sensor.

The space industry uses an agreed Technology Readiness Level (TRL) matrix to assess the maturity of new technologies prior to their incorporation in proposed spacecraft or instrument payloads. TRL’s range from the lowest level, TRL 1 where the basic principle is observed and reported, to TRL9 where the actual system is flight proven through a successful mission (ESA, 2008). This allows for realistic management of both science and engineering, providing a tool to help mitigate the risks imposed by performance, schedule and budget. The model philosophy adopted during the SPLIT research programme within MINAR is summarised in Fig. 4E and shows engineering evolution of the design to date. Early concept testing with the Beagle 2 Mole mechanism (Richter *et al.* 2003) enabled development of the Basic Breadboard (BBB), which was then refined and tested through to the current 3rd Generation Breadboard (3GBB).

#### Planetary exploration sample bags (University of Edinburgh)

The collection of samples that are free of human contamination is essential in planetary exploration, particularly when the focus is on organics and life detection, but as a general matter

samples that have minimal contamination is beneficial since contaminant biota and organics can change the geochemistry of rocks. This project was an initiative to use prior experience with commercially available sampling bags to design and test prototypes of an optimal planetary sampling bag. Several prototype bags were tested in the Mars Yard and they were compared with the existing Whirl-Pak™ bags generally used in field biological sampling. MINAR 5 was used to test the prototype sample bags in a field setting.

#### *Analytical instruments*

Analytical instrumentation was a suite of instruments designed to investigate samples after collection either for geological, geochemical or biological characteristics (Fig. 5).

[Figure 5 here]

#### Close-Up Imager (Space-X Institute, Switzerland)

CLUPI (CLose Up Imager) is one of the instruments of the ExoMars 2020 rover, a joint mission of the European Space Agency (ESA) and the Russian Federal Space Agency (Roscosmos) (Vago *et al.* 2013). CLUPI is a camera system designed to acquire high-resolution close-up images of geological samples, providing visual information similar to that a geologist would obtain using a hand lens (Josset *et al.* 2017). The images of sedimentary structures and rock textures produced with CLUPI will be crucial to select and contextualize the samples to be in turn analyzed with other instruments located within the rover. It is also designed to be used to study drill holes, drilling fines and drilled core samples delivered in the Core Sample Transportation Mechanism (CSTM) prior to sending to the instruments within the rover.

CLUPI is a powerful, miniaturized, low-power, efficient and highly adaptive system composed of three main parts: an optics with focus mechanism that allows the acquisition of

sharp images of any target from 10 cm to infinity, a colour (RGB) Active Pixel Sensor with  $2652 \times 1768 \times 3$  pixels, and a high performance integrated electronics system. The functionality of z-stacking (i.e. combining of many images acquired at different focus positions to generate an image that is sharp in all areas) is also implemented in order to increase the scientific return. The CLUPI analog instrument tested during the MINAR campaigns has the same image sensor as the instrument that will be on the ExoMars rover, although with different optics, which provide a slightly larger field of view ( $20^\circ$  instead of  $14^\circ$ ). The CLUPI Calibration Target (CCT, provided by Aberystwyth),  $2.5 \times 2.5 \text{ cm}^2$  in size, was also used.

During MINAR 5, science validation activities (i.e., preparatory activities done on Earth to test and train using the instrument) were performed (Fig. 5A). A collection of samples comprising a variety of evaporitic minerals were imaged with a CLUPI prototype, allowing the CLUPI science team to test their instrument with samples that have a texture, luster, color, and general morphology analogous to materials that will be of prime interest during the ExoMars mission. As hydrated salt minerals that share compositional, crystallographic and textural similarities with the evaporitic mineral constituting the Permian Zechstein sequence of Boulby mine (Woods 1979) have been identified on the surface of Mars (Barbieri and Stilvaletta, 2011), the materials examined in MINAR 5 provide a way to test the imaging capabilities of the CLUPI instrument.

#### UV Fluorescence spectroscopy (University of St Andrews/University of Aberystwyth)

Ultraviolet (UV) fluorescence spectroscopy can be used to examine samples for organics (which fluoresce in the UV radiation region) and minerals with fluorescence characteristics. Fluorescence excitation was carried out using a 280 and 365 nm LED, in complete darkness and at room temperature (Fig. 5B). An 0.22 NA optical fiber was positioned to collect light at approximately a  $90^\circ$  angle from the incident UV illumination. Emission spectra were measured



using an Ocean Optics JAZ spectrometer and reflected UV light was rejected by a Schott 395nm long pass filter (GG395). Data were recorded using SpectraSuite software, for wavelengths ranging from 350 to 750 nm. Imaging was obtained with a Thorslabs DCC1645C camera of 1.3 Megapixels (1280 x 1024) and 25mm f/1.4 lens mounted to view the sample surface at normal incidence from 200 mm. The lens was fitted with a Schott 410nm long pass filter (GG410) to reject reflected UV illumination.

MINAR 5 was used as an analogue field site validation test of Ultraviolet (UV) fluorescence spectroscopy with a specific focus on ancient salt samples with different geochemistries. The set-up prefigures the development of a dedicated and field oriented UV-camera, as a collaborative project between University of St-Andrews and University of Aberystwyth.

#### Raman spectroscopy (NASA Ames Research Centre)

Raman spectroscopy is planned on a number of missions including the ExoMars and the Mars2020 mission. This method is suited for the detection of organics and mineral determinations. An InPhotonics inPhotote Raman Spectrometer (model INP-3b-785ZZ) was used to characterize the mineral composition of various ancient evaporite minerals from different locations in Boulby mine (Fig. 5C). This instrument was supplied with a 785 nm excitation 350 mW Class IIb monochromatic red laser and has a fiber optics sampling probe enabling the laser light to pass through the sample under investigation. The resulting Raman scattering radiation is transferred to the spectrograph with corrected background radiation for subsequent data analysis.

MINAR 5 was used as an analogue field site validation test of Raman spectroscopy with a specific focus on ancient salt samples with different geochemistries.

### DNA Sequencing (NASA Jet Propulsion Laboratory)

DNA sequencing is a powerful way to study life in the deep subsurface, but also to assay subsurface environments and other sites of astrobiological interest for human contaminants. For example, it has been shown by Saul *et al.* (2005) that human activity-induced hydrocarbon contamination significantly changed the in-situ soil bacterial diversity near a field station in Antarctica. Understanding the contributions of human activities on microbial diversity of the pristine environments will help us understand Planetary Protection (PP) implications during human habitation on Mars.

DNA sequencing was performed in situ using a MinION sequencer (Oxford Nanopore Technologies, UK). The MinION from Oxford Nanopore Technologies is a compact, portable sequencer ideal for in-field nucleic acid sequencing during field expeditions (Fig. 5D). It sequences DNA and RNA strands by detecting changes in ionic currents caused by different nucleotide sequences as the strands pass through thousands of nanopores located on the flow cell of the MinION. Owing to its portability, it has been used in extreme, remote environments such as the International Space Station (Castro-Wallace *et al.* 2016) and Antarctica (Johnson *et al.* 2017) and it has been used as a genomic surveillance tool in West Africa during the Ebola outbreak (Quick *et al.* 2016). The low cost and simple library prep also make the MinION a good teaching tool for students (Jain 2016).

MINAR 5 was used as an analogue field site validation test of *in-situ* DNA sequencing. At the time of MINAR 5, it was the deepest in-situ DNA sequencing yet performed. MINAR 5 also provided the first opportunity to study microbial bioload in an underground laboratory to compare to other existing surface cleanroom facilities such as spacecraft assembly rooms and laboratories.

Five samples were collected in duplicate from different locations based on varying degrees of human activity around the underground laboratory. Sites with a high degree of

human activity were those near the laboratory entrance while samples collected far away from the laboratory had relatively low foot traffic. End-to-end sample collection, sample processing, DNA extraction, PCR, sequencing library preparation and DNA sequencing of microbial communities was performed in a cleanroom inside the laboratory.

#### Passive Air Sampler (NASA Jet Propulsion Laboratory)

The Rutgers Electrostatic Passive Sampler (REPS) passively captures biological airborne particles due to its permanently polarized ferroelectric films. The sampler is light, compact and can be deployed for long-term campaigns without supervision. It requires no electricity to operate. As power sources are limited in the mine, the REPS proved to be a convenient and nonintrusive method for monitoring airborne microbes.

REPS samplers were applied in the Boulby Potash Mine to demonstrate its efficiency in collecting airborne particles from an extreme, low biomass, environment. Samplers were deployed in duplicate in ISO6 and ISO7 cleanrooms inside the laboratory, six locations in the mine to compare between areas with little human presence and those frequented by humans. Data captured from the portable REPS sampler will help us understand airborne bacteria and fungi diversity present in the deep mine environment.

#### LAL/ATP analysis (NASA Ames Research Centre)

Both Limulus Amebocyte Lysate (LAL) and the Adenosine Triphosphate (ATP) assays are suitable for the detection of recent biological activity and were deployed in MINAR 5 to determine whether biosignatures of recent or older biological activity were present in the samples collected (Fig. 5E).

The LAL assay detects lipopolysaccharides (LPS), which are primary components in the cell walls of all Gram-negative microbes including active, dormant or dead cells. The LAL

chromogenic assay has been extensively used for quality control of pyrogens (Lipid A) in drugs. More recent, the LAL assay has been applied to bioburden monitoring in spacecraft (NASA Planetary Protection standard practices, NPR 5340, 2007), during field astrobiology trials (Maule *et al.* 2006a,b; Eigenbrode *et al.* 2009), and has been proposed for life detection for future planetary missions. The assay has been applied in biologically low biomass rocks and minerals ( $\leq 10^2$  cell equivalent/gram), to biomass-rich sediments and soils, i.e.,  $\sim 10^9$  cell equivalent/gram (Bonaccorsi *et al.* 2010).

LPSs were extracted from  $\sim 1$  gram of mineral, aseptically crushed and dissolved into  $\sim 3.5$  mL of doubly distilled water (DDW). The solution was subsequently vortexed (2 min), sonicated (10 min. at 40 °C), and centrifuged at high speed (6,400 g) for 15 minutes. At the end of each cycle, the LPS-enriched supernatant was transferred in a new 15mL vial, while the LPS-leached solid residue (pellet) underwent further extraction. This procedure was repeated three times to ensure cell breakage, fragmentation of the LPS-bearing cell membranes, thus to increase LPS dislodgement, homogenization, as well as its concentration and detection. The final 11 mL solution was centrifuged one last time for 20 minutes to obtain a clear supernatant. Four 25  $\mu$ L aliquots of this solution were pipetted into a lab-on-a chip cartridge (Sensitivity range 0.5-0.005 EU/mL, and 1.0-0.01 EU/mL) and analyzed with a Portable Test System (PTS) spectrophotometer (405-410 nm) (Fig. 5E). The chip has four ports receiving the liquid sample, two for spiked and two for non-spiked sub-aliquot samples. The resulting Endotoxin Unit (EU), 1EU=  $1 \times 10^5$  cell equivalent/mL of *Escherichia coli*, is translated into nanograms of LPS (ng/mL) using calibration curves built into the PTS's software. The current practical limit of detection for the LAL assay is 0.005 Endotoxin Units (EU), equivalent to ( $5 \times 10^{-13}$  g of LPS) per ml of water, or approximately 500 cells/mL. When necessary, such as with reaction-inhibited or enhanced samples, the solution was diluted from 10 to 1000 times with pyrogenic-

free LAL water, or a different sensitivity range's cartridge was used. Samples were run in quadruplicate, two different cartridges with two ports, each (N=4).

#### *ATP assay*

We estimated the living biomass in samples using the ATP assay in conjunction with a hand-held EnSURE Luminometer. The luminometer measures the light emitted by the luciferine-luciferase enzymatic reactions binding with the ATP released by living cells (e.g. Balkwill *et al.* 1988). Lighting events are translated into Relative Luminosity Units (RLUs).

The RLU values are directly translated into ATP biomarker concentration by using known dilutions of ATP (ATP salts) within the dynamic range of two types of device.

The Hygiena system assay uses honey dipper test devices, one for total ATP (AquaSnap Total) and one for Free ATP (AquaSnap Free) to quantify the labile ATP biomarker as a proxy for living cells. The Total ATP device contains an extraction agent to break down cells, releasing their ATP content. The two test devices are used together to determine the microbial load in liquid samples. We estimated the microbial ATP by processing 100  $\mu$ L aliquots of the same sample with the two sampling devices i.e., Cellular/Microbial ATP = Total ATP - Free ATP. The larger the difference, the more microbial ATP a sample contains.

For the analysis we used 1 to 10 g of rocks, or 1 mL of liquid brine sample. Ten grams of evaporites were dissolved in 30 mL of ddH<sub>2</sub>O in sterile 50 mL Falcon tubes. Liquid brines were diluted 100 to 1000 times in ddH<sub>2</sub>O. For each rock type and environment the appropriate dilution protocol was determined (until the best signal/noise ratio was achieved). Each sample was analyzed up to 3-4 times for free ATP and three times for free ATP.

MINAR 5 was used as an opportunity to test the LAL/ATP assay methods to investigate bioassay operation, procedures and results in ancient salt samples with different contamination conditions.

### Methane gas analyses (Newcastle University/Durham University)

The concentration and stable isotopic values of methane can give valuable information as to its source (such as microbial, thermogenic, abiogenic; e.g. Whiticar 1999). The concentration and carbon stable isotopic composition of methane at various points throughout the subsurface mine tunnels were analyzed, and methane was extracted from representative evaporite minerals (halite, polyhalite, potash) from the mine to test for potential biosignatures.

*Survey of methane (CH<sub>4</sub>) concentrations and  $\delta^{13}\text{C}$ -CH<sub>4</sub> isotope values.* Methane concentrations in the mine atmosphere were analysed at a total of 13 points in the mine tunnels. *In situ* concentrations were measured using an EcoTec TDL-500 portable tunable diode Laser Methane/Gas Analyzer (Geotechnical Instruments Ltd, Leamington Spa, UK). At each sampling point the instrument was left to equilibrate for 30s or more prior to readings being taken. The detection range was 0-10000 ppmv, and prior to analyses the detector was calibrated to a 500ppmv standard. At each analysis point, 5L of the mine atmosphere was additionally sampled into a gastight aluminium coated Tedlar bag (30274-U, Sigma) using a small battery powered air pump. The 5L bags were then transported back to the Boulby Underground Laboratory, stored overnight, and the <sup>12</sup>CH<sub>4</sub> concentrations (precision 5 ppb + 0.05% of reading <sup>12</sup>C ) and  $\delta^{13}\text{C}$ -CH<sub>4</sub> values (precision <0.8‰) measured on a Picarro G2201-i cavity ring down spectrometer (Picarro Inc, Santa Clara, CA). Samples with concentrations >100 ppm (over-range for high precision  $\delta^{13}\text{C}$ -CH<sub>4</sub> measurements) were diluted prior to  $\delta^{13}\text{C}$ -CH<sub>4</sub> analysis by injecting 200 ml of gas into a ~2L sample of air within a gastight Tedlar bag.

*Concentrations /  $\delta^{13}\text{C}$ -CH<sub>4</sub> values of methane extracted from representative Boulby Mine mineralogies.* Eight representative evaporite minerals representing the dominant lithologies at Boulby Mine (halite, potash, polyhalite) were broken up to grain sizes of ~ 1 to < 5 mm with a hammer, and 2.5 grams of each weighed into 5 ml borosilicate serum vials (Wheaton). Each

vial was sealed with a thick rubber stopper (Bellco) and crimp sealed with an aluminium top. The air within the vials was then connected via a needle and gastight tubing to a vacuum pump, and the air within the vials evacuated over a period of two minutes each. Once all the vials had been degassed, 40 ml of 5.0 grade helium (BOC) was added to each vial using a gastight syringe/needle. The helium was stored in a gastight 5L Tedlar bag prior to use. Twenty millilitres of 18.2 MΩ.cm water, previously purged of air by gassing with 5.0 Grade helium for 1 hour, was then added to the vials, and the vials shaken for 20 seconds. They were then left for an hour for mineral dissolution to occur prior to gas headspace analysis of the samples. From each vial, 20 ml of gas was extracted and analysed on the Picarro Surveyor P0021-S cavity ring down spectrometer described above.

The objective of MINAR 5 was to demonstrate the application of portable methane concentration and isotopic determination technology in the deep subsurface whilst acquiring new primary data. The work also showed the potential use of portable gas detection technologies for geology and astrobiology investigations by future explorers on other planetary bodies.

#### Metabolt (Luleå University of Technology)

Metabolt is a lightweight, robust, low-power, ultra-portable instrument to investigate, if present, the signature of life and quantify the metabolic activity in soil or regolith (Fig. 5F) (Zorzano *et al.* 2017). The instrument monitors the variability of the electrical conductivity, redox potential and gas concentrations of dominant metabolic by-products, oxygen and carbon dioxide. Simultaneously, environment parameters such as soil temperature, air temperature, air pressure, and relative humidity are also recorded. The instrument monitors in parallel the electrical properties and gas concentrations for two samples of which one is doped with glucose.

MINAR 5 was used as an analogue field site validation test. The main objective of the campaign was to validate the Metabolt instrument in an uncontrolled environment analogous to Mars and to operate the instrument with the salt samples available in the mine. A halite salt mixture was used that was deliberately collected from a highly human-accessed area recording highest number of DNA fingerprints in the PCR studies carried out by NASA JPL's scientists (see 'DNA sequencing').

### *Environmental analysis*

Environmental analysis instrumentation was a suite of instruments designed to monitor environmental conditions in sampling sites. These types of instruments can be deployed by explorers to assess the safety of sites, to map field sites, or they can be left for the long-term to monitor physical and chemical conditions in an extraterrestrial site of scientific interest (Fig. 6).

[Figure 6]

### In-Xpace 3D (Luleå University of Technology)

An essential instrument for future robotic and human exploration of the subsurface is 3D mapping. The Instrument for eXploration of space 3D (In-Xpace 3D) is a 3D mapping system developed using Red-Green-Blue (RGB) and an Infra-Red (IR) depth camera and the dense simultaneous localization and mapping (SLAM) ElasticFusion algorithm to generate a point cloud image. The In-Xpace 3D system provides a real time 3D imaging and post-sensing capability with a RGB-IR depth camera that can be used on astronaut helmets or mast of rovers for planetary exploration of geological features such as caves. The ability to operate in a low



light environment and the absence of complex post-processing to produce point cloud images, makes InXSpace 3D competitive to current 3D mapping techniques.

MINAR 5 was used as a field site validation test of 3D mapping in an underground space analogous to underground caverns of caves on the Moon and Mars. The technology was deployed in the Mars Yard to map the cavern itself and target rocks. It was also deployed in the polygons experimental area to map polygonal structures in the area in 3D. It was used to test 3D mapping under low light/dark conditions in real time exploration.

#### HABIT (Luleå University of Technology)

HABIT (HabitAbility, Brine Irradiation and Temperature) is a multipurpose instrument devoted to evaluating the habitability of Mars, but also an In-situ Resource Utilization instrument for future Mars exploration. It is approved for flight on the ESA ExoMars landing element. The objectives of HABIT are: a) to investigate (and quantify) the habitability of the landing site in terms of the three most critical environmental parameters for life as we know it: availability of liquid water, UV radiation biological dose, and thermal ranges (on Earth, microbial metabolism has only been found above 240 K and reproduction above 255 K); b) to provide environmental information (air and ground temperature, ground relative humidity (RH) and UV irradiance), to investigate the atmosphere/regolith water interchange, the subsurface hydration, as well as the ozone, water and dust atmospheric cycle and the convective activity of the boundary layer; c) to demonstrate an In-Situ Resource Utilization technology for future Mars exploration.

During a mission the instrument performs the following environmental and vessel measurements: (i) air temperature (x3); (ii) wind-activity (forced convection regimes); (iii) ground temperature; (iv) brine conductivities (x6); (v) vessel temperatures (x6); (vi) filtered-UV irradiances (x6). The instrument operates autonomously measuring at 1 Hz, with regular

acquisitions (about 5 to 10 minutes per hour plus one to four hours of extended continuous acquisitions as defined in the schedule table) during the day and in particular during the cold night hours, on a predefined schedule basis programmed by the SP Compute Element (SPCE). The instrument is able to autonomously heat each vessel to dehydrate the salt (regeneration) at night. By optimizing this, the amount of water captured at night is maximized to investigate future ISRU applications.

MINAR 5 was used as an analogue field site validation test of the HABIT instrument in a salt-rich environment. Tests conducted included the use of the following substrates in the HABIT cells: Test 1: Cell 1) 40% potash in halite; 2) pure halite; 3) rehydrated halite; 4) potash; 5) polyhalite; 6) 60% potash in halite. Test 2: Cell 1) 40% potash in halite; 2) stalactite sample (middle electrode); 3) rehydrated halite; 4) brine pool sample; 5) polyhalite; 6) 60% potash in halite.

#### PACKMAN (Luleå University of Technology)

PACKMAN is a small, robust, light, and scalable instrument that monitors gamma, beta, alpha radiation, and muons with two Geiger counters. This instrument includes environmental sensors to monitor pressure, temperature, relative humidity, and magnetic perturbations (with three fluxgate magnetometers in three perpendicular axes) and includes data archiving, GPS and communication capabilities. PACKMAN is an autonomous instrument that can be deployed at remote locations and send the data automatically through wireless communications. The PACKMAN-G (ground), installed at the Boulby mine, is adapted for surface monitoring, including outdoors remote operation, to provide simultaneous records at multiple latitudes (and longitudes) with different geomagnetic fields and at different heights with different total air column (pressure) and weather phenomena. Three ground-based indoor

versions of PACKMAN are installed in Kiruna (PACKMAN-K), Luleå (PACKMAN-L), and Edinburgh (PACKMAN-E).

MINAR 5 was used as a field site validation test of background particle monitoring in underground environments. The instrument was deployed long-term in Boulby to test robustness and reliability as part of a global PACKMAN network and to use the permanence of the underground laboratory to allow for long-term monitoring studies.

#### PES (Luleå University of Technology)

The Perpetual Environmental Station (PES) is a robust instrument, designed to last in harsh environmental conditions, with a suite of sensors for a long temporal study of the shallow region of the sub-surface environment and the surface parameters (temperature, pressure) over a wide spatial area. The PES has sensors oriented in a vertical fashion using a pole structure, installed at multiple depths for studying and characterizing the sub-surface environment. With a real-time data acquisition and communication, each station is self-sustaining.

MINAR 5 was used as a field site validation test of the PES in underground environments. The instrument was deployed long-term in Boulby to test robustness and reliability and to use the permanence of the underground laboratory to allow for long-term monitoring studies.

## **Results**

*Testing of planetary exploration technology (objective a).*

*Sample acquisition*

#### NASA Drill

Drilling into a polygon boundary in the polygons experimental area (Fig. 2) is shown in Fig. 7. Four holes were drilled: the first a trial blank hole cored to mechanically cleanout the corer;



the second into the polygon boundary junction; and the remaining two near a polygon's centre. For each hole, up to four minicores were drilled. The core samples were obtained in 7 cm increments (the corer length), with the drill string re-entering the same hole. Core cuttings created during drilling were collected into sterile 50 mL Falcon tubes. The total hole depth was measured with a ruler at the end of drilling and ranged from 20 cm to 37 cm. The core samples were cooled down in the encasing core string and directly sampled into sterile bags (Whirl-Pak™). Representative samples were processed for extraction of the target biomarker. The exercise successfully demonstrated the ability to acquire drilled samples from ancient halite samples using the prototype Mars IceBreaker drill string (McKay *et al.* 2013).




[Figure 7 here]

## SPLIT

As shown in Fig. 4, the MINAR field campaign has been crucial to developing and implementing key design features of the SPLIT device; this is summarised in Table 1 (impulse energy, impulse mechanism and tip geometry). By validation of the Basic breadboard (BBB), MINAR III directly informed the 2nd Generation Breadboard (2GBB) design, which was later verified during the UK Space Agency MURFI field trials in Utah (Balme *et al.* 2016). In 2017, MINAR V confirmed results obtained during the earlier MINAR III programme, and allowed preparation for ESA's CAVES/PANGAEA testing of new Lunar/planetary sampling protocols by astronaut Matthias Maurer (using the flight-like 3GBB SPLIT). Field testing is fundamental to this type of instrument development with MINAR III and V being critical to both the development of SPLIT, in terms of engineering, and writing the scientific protocols that enable the instrument. MINAR III was the first time that SPLIT was used outside the laboratory environment and thus met a TRL assessment criteria of testing in a representative environment

(thermal and vacuum environmental testing will be implemented at TRL 5 development). This was an important step for SPLIT because early field testing revealed nuances about SPLIT sampling, with analogue material, that had not been seen in specially prepared analogues for the laboratory. The Boulby analogues, used in situ during MINAR, provided a realistic and ‘natural’ presentation of rock that subsequently increased our confidence in the SPLIT technique and its efficacy for a given impulse energy.

Development /Design Feature	Basic Breadboard	*** 2 <sup>nd</sup> Generation Breadboard	3 <sup>rd</sup> Generation Breadboard
*Approx. date period	Nov 2013 – Aug 2015 (MINAR III April 2014)	July 2015 – Nov 2016	Jan 2017 – Dec 2017 (MINAR V Oct 2017)
Impulse energy	** 0.378 J & 0.945 J	1.35 J	1.35 J
Impulse mechanism	Impact	Machined spring with inclined helical cam hammer mechanism (flight design)	Machined spring with inclined helical cam hammer mechanism (flight design)
Tip	<p>Commercial tip ~ 60° tip; modified length of 60 mm</p>  <p>This image shows the commercial tip used to expose a pristine cross-mineral boundary of sylvite and sylvinites</p>	<p>Flight like design E4340 steel flight-like geometry</p> 	<p>As per 2GBB but including a forward bellows and housing.</p> <p>NB: The E4340 steel is heat treated for optimised strength characteristics. The geometry is designed such that the obtuse face will deflect particles parallel to the rock surface (during operations) and the acute feature minimises shock damage in the tip.</p>
Field testing	<b>MINAR III</b>	MURFI 2016	<b>MINAR V &amp; ESA's PANGAEA</b>
Geological materials	<p><u>Evaporites</u></p> <ul style="list-style-type: none"> <li>• <i>Boulby Potash (with sylvinites &amp; sylvite)</i></li> <li>• <i>Boulby polyhalite</i></li> <li>• <i>Boulby carnallite</i></li> <li>• <i>Boulby volkovskite</i></li> </ul>	<p><u>Sedimentary</u></p> <ul style="list-style-type: none"> <li>• <i>Conglomerate (fine sandstone matrix &amp; a coarse grain distribution of clasts up to approx. 3 mm).</i></li> <li>• <i>Sandstone (medium grain)</i></li> <li>• <i>Mudstone</i></li> </ul>	<p><u>Evaporites (MINAR) / basalts (PANGAEA)</u></p> <ul style="list-style-type: none"> <li>✓ <i>Boulby Potash</i></li> <li>✓ <i>Boulby Polyhalite</i></li> <li>• <i>Boulby Halite</i></li> <li>• <i>Lanzarote vesicular basalt</i></li> <li>• <i>Lanzarote basalt with gypsum veins</i></li> </ul>

		(very fine grain with gypsum veins)	
CAD rendering	 <p>Image shows the BBB used to determine optimum impulse energy through empirical testing in the laboratory and at the Boulby Mars Yard during MINAR III</p>	 <p>The 2GBB tip and spring constant were based, in part, on MINAR III test results and used a flight type mechanism to actuate the impulse.</p>	 <p>The 3GBB was first tested during MINAR V. Additional key feature are the forward bellows and body that enabled first time aseptic field tests of this kind with a SPLIT tool and demonstration of tele-operation by an ESA astronaut, as might be adopted on the Moon or Mars.</p>
Notes	<p>* Dates refer to STFC/UK Space Agency grant dates with specific field tests in parenthesis ( )</p> <p>** Early concept testing with the Beagle 2 Mole mechanism used a calculated impulse energy of 0.378 J that was used as an engineering baseline for SPLIT development.</p> <p>*** The 2GBB was not specifically used during MINAR</p>		

**Table 1.** The use of MINAR campaigns to advance SPLIT development

### Universal Planetary Sampling Bag

Many field expeditions, particularly those collecting samples aseptically for biological sampling, make use of the ‘Whirl-Pak™ bag’, a sterile sampling bag originally patented for the purpose of transporting milk. Although the bag has found very wide use in field expeditions because it is commercially available, it is apparent to anyone who uses it that it suffers from several flaws that reflect the lack of design for field sampling.

In view of these flaws, we set about to identify the major problems with existing bags and to identify solutions to them (Table 2). With these solutions in mind, we fabricated prototype Universal Planetary Sampling Bags and optimised them based on testing in the

MINAR 5 campaign. The resulting prototype design is shown in Fig. 8A with photographs illustrating the steps in its use (Fig. 8C to F).

There are variants of the bag that were tested, including replacing the internal sample acquisition flaps with a glove (Fig. 8G). However, given different hand and glove sizes, it was deemed that simple internal flaps were more effective and they provided sufficient purchase to obtain samples. Problems encountered attempting to fit a hand into a glove also had a tendency to rip the bag.

From these trials, we suggest the fabrication of a bag for human exploration missions with the characteristics described in Table 2 and illustrated in prototype form in Fig. 8A,B.

**Table 2.** Problems with conventional Whirl-Pak™ sampling bags for field exploration solved with the Universal Planetary Sampling Bag.

	<b>Problem with Whirl-Pak™ and other conventional sterile bags</b>	<b>Solution in Universal Planetary Sampling Bag</b>
1	Separate piece of plastic removed to open bag that can be lost in the field site or causes operational difficulty	Perforation within bag and attachment of two flaps to bag that are not removed. No loose material from the use of the bag
2	Small flaps make it difficult to operate in bulky gloves in extreme fields sites	Large flaps allowing for easy opening and closing of bag
3	Plastic is thin and liable to perforation with sharp rocks	Tough plastic used to minimise damage from geological samples
4	Difficult to get sample into bag	Internal plastic flaps that can be accessed on the underside of the bag and used to manually grab sample and retrieve it back into the bag
5	When bag is closed air gets trapped	Use of one-way air valve allows air to be squeezed out of bag automatically as it is closed

[Figure 8 here]

*Analytical instruments*

CLUPI

The CLUPI instrument was successfully used to image a range of evaporitic deposits that now form a library of such minerals acquired with calibration targets. Materials included the three primary evaporite types (halite, potash and polyhalite; Fig. 9A-D) as well as surfaces in the polygons experimental area (Fig. 9E), and secondary halite minerals from the brine sampling experimental area (Fig. 9F). Over 75 images of different materials were acquired. These analyses and image library provide information in addition to that already gathered in the MINAR 2-3 campaigns (Josset *et al.* 2014; Payler *et al.* 2016; Josset *et al.* 2017) and other CLUPI field tests.

In addition, MINAR 5 was an occasion for members of the CLUPI science team to collaborate with other scientific teams that performed geochemical and spectral analyses on the same samples photographed with CLUPI. This situation provided ideal conditions to train and simulate activities analogous to those that take place during rover missions generally and specifically at the Rover Operating Center (ROC) during the ExoMars mission. The CLUPI images are intended to contextualize and interpret the results obtained with the bulk analysis that will be performed within the rover. It is therefore crucial to understand what morphological details are relevant for the other teams and learn to create the most profitable synergy.

[Figure 9 here]

#### UV fluorescence spectroscopy

UV Fluorescence is a phenomenon where UV photons/matter interactions cause electronic transitions to higher-energy states, following by a quick (less than  $10^{-9}$ s) de-excitation and light emission in the visible range. Fluorescence can be produced by point defects, impurities, organic radicals and dislocations, all considered as emitters (or centres). The objective of MINAR 5 was to test UV fluorescence spectroscopy on ancient evaporitic materials and its



potential for field use to identify evaporitic minerals. The materials studied with CLUPI were further investigated in the underground laboratory. Fig. 10. Shows representative images under different UV illumination and their spectra. Fig. 10A, B and C show some of the UV illuminations obtained for halite, potash, and polyhalite. Overall, and especially at 365nm, illumination is limited. Only polyhalite exhibits a bright signature in the orange at 365 nm (Figure 10C). Figure 10D presents some of the results obtained for halite, polyhalite and potash, for a UV excitation at 365 nm. Overall, the three spectra are distinctive, and yet show a strong component between 600 and 650 nm. In alkali halides, the emitter in this region is generally  $\text{Mn}^{2+}$ , present between 571 and 647 nm (Delumyea *et al.* 1976, MacRae and Wilson 2008).  $\text{Mn}^{2+}$  could be present as impurity in interstitial position (Gorobets and Rogojine 2002). As  $\text{Mn}^{2+}$  is not a strong light-absorber, only highly concentrated minerals exhibit a sharp color (Platonov 1979). As UV fluorescence is a sensitive spectroscopy, this may explain why polyhalite, despite being uncoloured in the visible, shows a strong  $\text{Mn}^{2+}$  component. Moreover, halite shows a broad emitter, previously observed in halite but still unspecified (CSIRO database, MacRae and Wilson 2008). The shoulder observed in polyhalite at 580 nm could account for the presence of the same, but unidentified emitter. With such a shoulder, polyhalite appears more like a “mix” of the halite and the potash signatures. Finally, the resemblance between potash and the halite observed here is predictable, considering the structural similarities of their primary components (respectively KCl and NaCl). As well as having similar hardness (considered as soft - under 20 kg mm<sup>-2</sup>), they also exhibit the same crystal structure (CFC), the same slip-system, and despite being non-identical, they share similar electronic properties (Pool *et al.* 1975).

These data demonstrate that the three primary evaporite minerals found at Boulby can be distinguished using UV fluorescence spectroscopy and that distinct peaks in fluorescence

could be used in planetary environments to disentangle single or mixed deposits of evaporitic materials comprised chloride or sulfate salts.

[Figure 10 here]

### Raman spectroscopy

Raman analysis of evaporite samples showed the expected featurelessness of the halite (Fig. 11). No distinguishing peaks were observed. Broad peaks were observed in some samples, which may be caused by iron oxide or clay inclusions. However, polyhalite showed two characteristic peaks associated with sulfate. These peaks are consistent with similar peaks observed previously in this material (Payler *et al.* 2016). The Raman analysis shows the potential for effective analysis of evaporite minerals. However, the data also show that halite, because of its featureless spectrum, cannot be readily identified by the method. These results highlight the need to use multiple methods (such as UV fluorescence) to achieve identification of halite evaporites, particularly if they are mixed with evaporites such as sulfates that have distinguishing features and will swamp the presence of these other minerals.

[Figure 11 here]

### DNA sequencing

DNA sequencing technology tests focused on samples that would yield insights into the bioload associated with an underground clean laboratory as a comparison to surface clean laboratory sites. Five samples were collected in duplicate from different locations based on varying degrees of human activity around the laboratory. Sites with a high degree of human activity were those near the laboratory entrance while samples collected far away from the laboratory

had relatively low foot traffic. End-to-end sample collection, sample processing, DNA extraction, PCR, sequencing library preparation and DNA sequencing of microbial communities was successfully performed in a cleanroom inside the laboratory. In addition to in-situ collection, the JPL team collected samples of evaporite minerals from the Boulby Mine for biosignature detection using metagenomics and planetary instruments. Microbial signatures in these samples will be detected at JPL using next-generation DNA sequencing and bioinformatics analysis. The mineral samples will be scanned by SHERLOC and PIXL instruments planned for the Mars2020 mission for biosignature detection at JPL. Post-SHERLOC and PIXL analysis, we will perform an in-depth metagenome analysis of these same samples to understand the extent of microbial and eukaryotic diversity and their functional capabilities. This comparative analysis is imperative for verifying biosignature detection capabilities of future life detection instruments.

#### LAL/ATP analysis

LAL and ATP assays were successfully used to examine samples from the mine. Samples collected in a non-sterile way were found to contain markers. For example, polyhalite samples collected by mine personnel for the purposes of MINAR 5 (Samples 2-4) yielded values between 0.0028 and 0.011 nanograms LPSs per gram (ng/g) as well as ~10 to 113 fMoles of total/free ATP per gram of rock. High concentrations were observed in the brine pool area that has seen human activity. Specifically, the white evaporitic crust collected from the brine pool's shoreline yielded ~ 0.1 nanogram LPS per gram of sample. Four brines analysed showed values that ranged from a minimum concentration of LPS at 0.73-2.0 ng per mL and 0.15-0.18 ng/mL to maximum concentrations of this biomarker at between 5.22-5.75 ng/mL. Two of these brines yielded the highest amount of total ATP  $453 \pm 31$  and  $8200 \pm 938$  fmoles/mL including 9% to 23% of microbial ATP, respectively. The highest percentage proportion of microbial ATP was

found in the contaminated ground of the laboratory entrance (53%) and in the secondary modern evaporites (stalactites and concretions) from the brine pool's wall with 42% and 46% microbial ATP, respectively.

The lowest concentration of measurable LPSs were found associated with the polygons where strict sterile drilling was observed. Only one out of three replicates of Sample 9B, cored from the clay-rich polygon margin, yielded concentrations above the LPS detection limit i.e., 0.055 ng/g of halite rock. Non-measurable Lipid, below the limits of detection ( $<0.005$  EU/mL) were found in the clay-free samples drilled from the polygon's center (Sample 9A). However, these samples were positive for free ATP, which comprised 100% of the total ATP (Fig. 12B). The absence of microbial ATP rules out contamination during drilling and sample handling. Clay-barren and clay-rich halite from the polygon center and clay-rich polygon margin yielded ~180 to 280 fmoles per gram of total ATP, respectively, perhaps reflecting some preservation of relatively modern biomarker in the halite and clay-rich matrix.

[Figure 12 here]

MINAR 5 thus provided a demonstration that aseptic drilling can be accomplished in ancient evaporites using basic decontamination methods without contamination detectable by this assay. It also allowed us to optimise LAL/ATP assays for use by human explorers to monitor the movement of contamination in areas of human habitation on other planetary surfaces.

### Metabolt

MINAR 5 was used to carry out analogue field tests of the Metabolt instrument demonstrating its operability in uncontrolled remote environment. Fig. 13 shows an example of a MINAR 5

experiment where two samples of crushed halite from the mine were monitored over 5 days in the mine, after the addition of 40 ml of water. Each sample was incubated independently in one container. In one of them, glucose was added as an organic carbon source, diluted in 40 ml of water with a 0.5% concentration by volume. During the first four days of incubation there was a smooth evolution of the electrical conductivity (Fig. 13A), redox (Fig. 13B), carbon dioxide gas (Fig. 13C) and oxygen (not shown). The redox value showed a significant transition on the 16th to 17<sup>th</sup>. During this time, both experiments showed an emission of carbon dioxide and a strong consumption of oxygen (Fig. 13C-inset). This was coincident with sudden changes in the electrical conductivity, which may be attributed to release of products during metabolic activity.

The MINAR 5 analogue campaign allowed the in-situ demonstration of Metabolt capabilities as an instrument to monitor metabolic activity of samples within their natural environment. Metabolt is a promising technology for life exploration on Mars or analogue environments on Earth, including simulation chambers.

[Figure 13 here]

### *Gas analysis*

The MINAR 5 campaign allowed the *in situ* analysis of mine atmosphere CH<sub>4</sub> and  $\delta^{13}\text{C-CH}_4$  at various points within the tunnels. A plot of CH<sub>4</sub> versus their  $\delta^{13}\text{C-CH}_4$  values indicates that the methane within the mine tunnel atmosphere is most simply explained by a mixture of thermogenic CH<sub>4</sub> (with a  $\delta^{13}\text{C-CH}_4$  between -33.6 to -34.3 ‰) and atmospheric surface derived air CH<sub>4</sub> (~ 47 ‰; Whiticar 1999) (Fig. 14). The thermogenic (i.e. thermally altered organic matter of previously biological origin) CH<sub>4</sub> is most likely derived from underlying hydrocarbon source rocks, which form economic deposits within the North Sea (Hitchman *et al.* 1989).

[Figure 14 here]

The pilot study to extract CH<sub>4</sub> from representative evaporite minerals was successful, with above background concentrations of CH<sub>4</sub> extracted from the two potash samples, but not from the halite or polyhalite minerals (Fig. 15). Unfortunately, the peak concentrations of CH<sub>4</sub> from the potash (402 ppm and 136 ppm) were too high to allow quantitative  $\delta^{13}\text{C}$ -CH<sub>4</sub> analysis (samples with concentrations > 100 ppm required dilution in the analytical set-up that we used). Nonetheless, these results suggest that CH<sub>4</sub> is concentrated only within certain mineral layers (potash) within the mine, and not others. This CH<sub>4</sub> may represent the partial trapping of upwelling thermogenic methane identified in the mine tunnel atmosphere, although further research is required to quantitatively test this hypothesis. Knowledge that methane gas is concentrated within certain mineral horizons could potentially aid future mineral exploration in the area (e.g. *via* the analysis of gases from boreholes).

MINAR 5 also demonstrated the deployment of methane collection and analytical instrumentation and data acquisition and analysis in a simulated planetary exploration scenario. Similar spatial analysis of methane could be carried out by human explorers on the surface and in subsurface deployments on Mars.

[Figure 15 here]

### *Environmental monitoring*

#### 3D mapping

The MINAR 5 campaign provided an opportunity to test the InXSpace3D instrument. Close-range mapping of salt rocks (Fig. 16A) and long-range mapping of the surface features of the

mine shaft walls (Fig. 16B) was carried out in the Mars Yard. In Fig. 16A, the inner square on top left shows the halite rock specimen that was taken for the close-range 3D mapping analysis. The camera was positioned about 0.5m above the specimen in the Nadir view. The DEM (Depth Elevation Model) analysis shows the capability of the system to resolve the surface features of the specimen to close tolerances. In the long-range mapping, the camera was moved in a rectilinear motion pointing towards the mine shaft walls. From Fig. 16B, the DEM analysis reveals the features that could be observed from a distance of 1.2 m. The box structure observed in the lower right portion of Fig. 16B shows the PACKMAN module installed in the Boulby Mine during the MINAR 5 campaign. The testing of the low cost, quick 3D mapping InXSpace 3D system in the MINAR 5 campaign validated the short-range and long-range capability of the system for deep subsurface exploration and mapping of terrestrial and extraterrestrial environments both in lit and dark conditions.

[Figure 16 here]

### HABIT

The HABIT instrument was operated during MINAR 5 using Permian halite to test the efficacy of the instrument using natural salts. After the several days, continuous operation of HABIT in the MINAR 5 campaign, corrosion was observed in some electrodes. This experience has led to modifications of their material, as well as their electronic paths in order to remove capillarity effects, which were also observed during the campaign. Thus, the MINAR 5 campaign both provided additional testing of the HABIT instrument and specifically identified required improvements in design that are to be implemented prior to future spaceflight.

### PACKMAN and PES

PACKMAN was installed in the Boulby Mine during the MINAR 5 campaign to study the low radiation environment and make a comparative study with a similar instrument operating on the surface of the Boulby Mine. The Fig. 17 shows the average particle count recorded by Geiger 1 of the PACKMAN operating on the surface and the average counts recorded by the Geiger 1 of the PACKMAN in the mine. A 12-minute moving average has been taken to smoothen the plot. The radiation ‘quietness’ of the mine owing to the kilometre of crust that shields the mine tunnels from the background radiation can be observed. These data and operations show the validity of deploying the PACKMAN as a radiation sensor in human habitats on and under other planetary surfaces. PACKMAN has been left within the mine to provide remotely accessible background particle data in the mine environment and to test remote access capabilities over a long time period.

[Figure 17 here]

The Perpetual Environmental Sensor (PES) was also deployed in the mine for long-term monitoring. The PES modules have been installed during the MINAR 5 campaign for a technological demonstration of operation of a wide range of sensors for studying sub-surface parameters. At present, the modules are not buried below the sub-surface and are just placed on the sub-surface to measure the long-term operability of the modules.

#### *b) Astronaut operations.*

During MINAR 5, European Space Agency astronaut Matthias Maurer took part in a week of activities. His work during this period included: taking part in field trips to brines and evaporite polygon structures to understand the motivations and work of the scientists involved in MINAR; working alongside different instrument teams to understand the use and rationale of



instruments being tested for robotic and human missions and particularly those instruments approved for flight on robotic missions; and taking part in live outreach links from MINAR.

### *c) Education*

Capitalizing on the unique environment of the mine, the teachers taking part in MINAR 5 focused on a developing a classroom Extra Vehicular Activity (EVA) activity. The EVA activity is a flexible classroom activity designed to teach sampling techniques used in obtaining biological and geological samples in planetary exploration. During the activity, students learn numeracy and literacy skills, group collaboration in carrying out scientific research, and critical thinking skills needed to explore our world and reach new levels of understanding of the universe at large. To begin setting the parameters for the EVA activity, teachers accompanied MINAR researchers on sampling excursions into various mine environments, included brine pools and polygon formations. Teachers benefitted especially from observing real time sampling procedures and they made evaluations for realistic classroom adaptations by collaborating with researchers in the field. Collaboration of teachers across disciplines broadened the scope of curriculum writing and added ways of making EVA activities and sampling activities more interesting and understandable to various types of learners.

Beyond the more focused work of writing lesson plans, the teachers were exposed to the application, communication, and reflection on the nature of science and the scientific method. Conversations with researchers on how projects were developed, tested and implemented highlighted how scientific reasoning is fundamental to their projects and how to incorporate this into the EVA activity.

The EVA activity involves breaking the class into groups, including a mission control and an EVA team. The mission control and EVA team communicate with one another as the EVA team go about collecting samples. These sampling protocols could be sampling biology,

geology, taking environmental measurements, or any activity consistent with the learning objectives for a given class or stage of learning. The class reconvene to discuss the results and conclusions. Thus, the EVA lesson plan consists of a core EVA plan for use in any classroom and ‘bolt-in’ EVA activities that can be developed by teachers for any given science learning objective. The material was written to be appropriate for primary or secondary schools.

#### d) *Outreach*

A total of 17 live interviews were undertaken during MINAR. The interviews included three one-hour overviews of the MINAR activities and 11 shorter interviews with members of MINAR 5 covering a variety of the instruments being tested (some of these videos are available on YouTube). The live links were streamed through Facebook. Fourteen days after MINAR, the mean number of views of these interviews was 8,503 (standard deviation 12,441) with a maximum of 38,000 and a minimum of 240. Successful live links to schools, colleges and the Dr APJ Abdul Kalam Technical University through the Kalam Centre in New Delhi, India were made, demonstrating the value of real-time education from a deep subsurface science laboratory. Accepting the time delay, these types of lecture and show-and-tell activities from an analog environment demonstrate not only the ability to do effective remote educational outreach from analog environments on Earth, but the potential for future outreach from subsurface laboratories and stations on the Moon and Mars and the enormous intrinsic interest they capture among science and engineering students and the general public.

In addition to MINAR-led activities, MINAR was also covered by the BBC News (Look North), Channel 4 national news, the BBC World Service and other internet news outlets.

## **Discussion**

Deep subsurface environments on other planetary bodies provide access to samples and measurements of interest for understanding the origin, history and potential habitability of those bodies (Boston *et al.* 1992; Cushing *et al.* 2007; Hofmann 2008; Williams *et al.* 2010). Furthermore, large natural subsurface caverns provide potential locations to situate future human habitats. We have used the Boulby Mine in the UK, a one kilometre deep active mine in Permian evaporite deposits, as a place to carry out science and test instruments and operational approaches for the robotic and human exploration of the deep subsurface (Bowler *et al.* 2013; Cockell *et al.* 2013; Payler *et al.* 2016).

MINAR 5 successfully undertook a coordinated campaign involving 42 individuals. The scientific focus of the campaign was the study of evaporite minerals and life detection. The instruments tested during the campaign included sample acquisition methods, non-destructive and destructive sample analysis methods and environmental monitoring equipment. We found that the organisation of these methods and instruments into a sequence of steps allowed us to bring together diverse sample acquisition and analysis methods into a coordinated campaign of experimental testing.

As well as in-situ investigations, the MINAR campaign created a diversity of sample analysis and instrument development objectives that will continue after the MINAR campaign. They include: study of biosignatures in ancient salt salts collected during MINAR (NASA JPL), study of microbial distribution and aerobiology using air sampling devices and samples obtained in MINAR (NASA JPL), optimisation of the robotic hammer, SPLIT (University of Leicester), optimisation of drills for future exploration based on experiences in MINAR (NASA Ames Research Center), optimisation of robotic instrumentation including the ExoMars rover CLUPI, HABIT instruments based on experiences during MINAR (Space-X Institution and Luleä University of Technology), advancement of new instrument improvements such as UV fluorescence spectroscopy (St Andrews University/Aberystwyth

University). These activities show that analog campaigns are not an isolated activity, but rather they provide real testing that leads to further studies of acquired samples and optimisation of instruments.

One advantage of running an analog campaign in an active commercial setting is the possibility for exploring direct links with Earth-based challenges. Two concerns in active mining environments are the collapse of the roof and the build-up of gases. The collapse of the roof is a general ongoing safety concern, but it may also occur in places that a mine wishes to bring back to economic activity and thus requires exploration capability to investigate the state of an environment. The build-up of gases is a concern since in some mines gases are explosive or, in the specific case of mines like Boulby, they can cause the blow-out of material during the release of pressure. During MINAR, the use of 3D visible and infra-red mapping technologies and the study of gases, including methane, enclosed within salts will advance potential approaches to improving rapid structural studies in mines and in the specific case of Boulby, understanding the location and source of gases that are of safety concern. A spin-off from MINAR 5 was the acquisition of funding by the Luleå University of Technology to design and build a rover to be deployed in the mine with 3D mapping, gas detection sensors and other instrumentation based on work conducted during MINAR 5. The rover will be tested in the Mars Yard with the objective of further advancing the link between astrobiology instrumentation for the subsurface exploration of other worlds and the advancement of technology to improve the economic efficiency and safety of mining activity on Earth. In the future, these links may even come full circle with potential links to mining of asteroids and other extraterrestrial resources. This rover will be deployed in the context of future MINAR events.

MINAR also allowed for the deployment of permanent instrumentation within Boulby with subsurface mining and future subsurface astrobiology applications. The Perpetual

Environmental Sensor instrument and the PACKMAN particle detector were deployed and linked into the internet during MINAR and left for long-term monitoring of the mine environment and its geophysical conditions. In particular, the PACKMAN instrument in Boulby is part of a global network of these instruments being developed and deployed by the Luleå University of Technology showing how an analog environment can be used as a site to deploy instruments that are part of global monitoring and planetary exploration studies.

In MINAR we worked in collaboration with the European Space Agency (ESA) CAVES and PANGAEA Programmes: geology and astrobiology training and testing programmes using analogue field sites such as caves and lava tubes in Lanzarote to train astronauts. During MINAR, ESA astronaut Matthias Maurer was able to work with different instrument and science teams on a daily basis to learn a variety of new methods and techniques for the human exploration of other planetary bodies. An advantage of the analog environment and campaign are the opportunity for astronauts involved in planetary exploration to gain rapid insight in a large number of activities and instruments that are localised to the analog site for the duration of the campaign.

MINAR demonstrates how an analog field campaign can be used as a mechanism to develop new curriculum materials. In the case of MINAR 5, educators were able to follow instrument teams and carry out field investigations and they were able to use this information to develop a classroom EVA activity. The field excursions provided ideas and concepts for field excursion and sample analysis activities that could be carried out by students in a simulated EVA activity. In particular, much consideration was given by the educators to the scientific method and how a classroom EV activity can be used to teach students concepts in carrying out good science such as appropriate controls, collecting multiple samples, problems with noise (contamination), sample analysis etc. We conclude by noting the additional value

for little extra effort that incorporating the development of curriculum materials into planetary field activities can achieve.

## **Acknowledgements**

We thank the Science and Technology Facilities Council (STFC) for their support of the Boulby Underground Science Facility in which MINAR 5 was conducted. Knowledge gained in the execution of STFC grant, ST/M001261/1, was used to advance objectives in MINAR 5. We thank Cleveland Potash and ICL for their generous in-kind and logistics support to MINAR and the underground science facility with which MINAR is made possible. Boris Laurent is funded by a Leverhulme Trust Research Project Grant, RPG-2016-071. SPLIT Research and Development has been funded by three research grants (UKSA CREST and STFC's Follow on Fund) between 2013 and 2017, with support in 2018 by CREST to realise a TRL 5 flight type prototype instrument. Jon Telling (gas analysis development) is funded in part by UK Space Agency grant ST/R001421/1.

## **References**

- Andrews-Hanna, J.C., Zuber, M.T., Arvidson, R.E. & Wiseman, S.M. (2010). Early Mars hydrology: Meridiani playa deposits and the sedimentary record of Arabia Terra. *Journ. Geophys. Res.* **115**, E06002.
- Balme, M.R. *et al.* (2016). UK Space Agency: Mars Utah Rover Field Investigation 2016 (MURFI 2016): Overview of Mission, Aims and Progress," 48th Lunar and Planetary Science Conference, 2017.

- Balkwill, D.L., Leach, F.R., Wilson, J.T., McNabb, J.F. & White, D.C. (1988). Equivalence of microbial biomass measures based on membrane lipid and cell wall components, adenosine triphosphate, and direct counts in subsurface aquifer sediments. *Microb. Ecol.*, **16**, 73-84.
- Barbieri, R. & Stivaletta, N. (2011). Continental evaporites and the search for evidence of life on Mars. *Geological Journal*, **46**, 513-524.
- Bettini, A. (2011). Underground laboratories. *Nuclear Instruments and Methods in Physics Research Section A: Accelerators, Spectrometers, Detectors and Associated Equipment*. **626-627**, S64-S68.
- Bonaccorsi R. & Stoker C. R. (2008). Science results from a Mars drilling simulation (Rio Tinto, Spain) and ground truth for remote science observations. *Astrobiology* **8**, 967-985.
- Bonaccorsi, R., McKay, C.P. & Chen, B. (2010). Biomass and habitability potential of clay minerals- and iron-rich environments: Testing novel analogs for Mars Science Laboratory landing sites candidates. *Phil. Mag.*, **90**, 2309.
- Boston, P.J., Ivanov, M.V. & McKay, C.P. (1992). On the possibility of chemosynthetic ecosystems in subsurface habitats on Mars. *Icarus*, **95**, 300-308.
- Bowler, S. (2013). From outer space to mining. *Astron. Geophys.* **54**, 3.1.-3.3.

- Bridges, J.C. & Grady, M.M. (1999). A halite-siderite-anhydrite-chlorapatite assemblage in Nakhla: mineralogical evidence for evaporites on Mars. *Meteorit. Planet. Sci.*, **34**, 407–415.
- Bridges, J.C. & Grady, M.M. (2000). Evaporite mineral assemblages in the nakhlite (martian) Meteorites. *Earth Planet. Sci. Lett.*, **176**, 267–279.
- Castro-Wallace, S.L. *et al.* (2017). Nanopore Sequencing and Genome Assembly on the International Space Station. *Scientific Reports*, **7**, Article number: 18022.
- Clark, B. C. *et al.* (2005). Chemistry and mineralogy of outcrops at Meridiani Planum. *Earth Planet. Sci. Letters* **240**, 73-94
- Cockell, C.S., Payler, S., Paling, S. & McLuckie, D. (2013). The Boulby International Subsurface Astrobiology Laboratory. *Astron. Geophys.*, **54**, 2.25–2.27.
- Cushing, G.E., Titus, T.N., Wynne, J.J. & Christensen, P.R. (2007). THEMIS observes possible cave skylights on Mars. *Geophys. Res. Lett.* **34**, L17201.
- De Angelis, S.H. (2017). Earth science at the UK's deepest laboratory. *Geology Today* **33**, 132-37.
- De Sanctis, M.C. *et al.* (2016) Bright carbonate deposits as evidence of aqueous alteration on Ceres. *Nature*, **536**, 54-57.



- Delumyea, R. G. & Schenk, G. H. (1976). Lead (II)-manganese (II) energy transfer in sodium chloride pellets. *Analytical Chemistry*, **48**, 95-100.
- ESA (2008). Technology Readiness Levels Handbook for Space Applications.
- Ehlmann, B.L., Mustard, J.F., Murchie, S.L., Bibring, J.P., Meunier, A., Fraeman, A.A. & Langevin, Y. (2011). Subsurface water and clay mineral formation during the early history of Mars. *Nature* **479**, 53-60.
- Eigenbrode, J., Benning, L.G., Maule, J., Wainwright, N., Steele, A., Amundsen, H.E.F. & AMASE 2006 Team. (2009). A field-based cleaning protocol for sampling devices used in life-detection studies. *Astrobiology*, **9**, 455-465.
- Gorobets, B.S. & Rogojine, A.A. (2002). Luminescence spectra of minerals. All-Russia Institute for Mineral Resources (VIMS), 78 Moscow.
- Hitchman, S.P., Darling, W.G. & Williams, G.M. (1989). Stable Isotope Ratios in Methane Containing Gases in the United Kingdom. British Geological Survey Technical Report WE/89/30.
- Hofmann, B.A. (2008). Morphological biosignatures from subsurface environments: recognition on planetary missions. *Space Sci. Rev.* **135**, 245-254.
- Hynek, B.M., Osterloo, M.K. & Kierein-Young, K.S. (2015). Late-stage formation of Martian chloride salts through ponding and evaporation. *Geology* **43**, 787–790.

- Jain, M., Olsen, H.E., Paten, B. & Akeson, M. (2016). The Oxford Nanopore MinION: delivery of nanopore sequencing to the genomics community. *Genome Biology* **17**, 239.
- Johnson, S.S., Zaikova, E., Goerlitz, D.S., Bai, Y. & Tighe, S.W. (2017). Real-Time DNA Sequencing in the Antarctic Dry Valleys Using the Oxford Nanopore Sequencer. *Jour. Biomol. Techniques*, **28**, 2–7.
- Josset, J.L., Souchon, A., Josset, M. & Cockell, C.S. (2014). ExoMars CLUPI Instrument Testing at MINAR II. EPSC Abstracts, EPSC2014-658.
- Josset, J.L. *et al.* (2017) The Close-Up Imager onboard the ESA ExoMars rover: Objectives, description, operations, and science validation activities. *Astrobiology* **17**, 595-611.
- Langevin, Y., Poulet, F., Bibring, J.P. & Gondet, B. (2005). Sulfates in the north polar region of Mars detected by OMEGA/Mars Express. *Science* **307**, 1584–1586.
- MacRae, C. M. & Wilson, N. C. (2008). Luminescence database I—minerals and materials. *Microscopy and Microanalysis* **14**, 184-204.
- Martínez, G.M. & Renno, N.O. (2013). Water and brines on Mars: Current evidence and implications for MSL. *Space. Sci. Rev.* **175**, 29–51.
- Martin-Torres, F.J. *et al.* (2015). Transient liquid water and water activity at Gale crater on Mars. *Nature Geosci.* **8**, 357–361.

Maule, J., Toporski, J. & Steele, A. (2006a). How lively are volcanic hot spring environments?

In situ field analysis in Kamchatka, Russia. *Astrobiology* **6**, 209.

Maule, J., Steele, A., Burbank, D., Eppler, D., Kosmo, J., Ross, A., Wainwright, N., Child, A.,

Flores, G., Monaco, L. Graziosi D. & Splawn, K. (2006b). Monitoring forward contamination during simulated surface extra-vehicular activity (EVA) at Meteor Crater, Arizona: Implications for human exploration of the moon and Mars. *Astrobiology* **6**, 275.

McKay, C.P. *et al.* (2013). The Icebreaker Life Mission to Mars: A search for biomolecular evidence for life. *Astrobiology* **13**, 334-353.

McLennan, S.M. *et al.* (2005). Provenance and diagenesis of the evaporite-bearing Burns formation, Meridiani Planum, Mars. *Earth Planet. Sci. Letters* **240**, 95-121.

Michalski, J.R. & Nils, P.B. (2010). Deep crustal carbonate rocks exposed by meteor impact on Mars *Nature Geosci.* **3**, 751-755.

Miller, D., Bonaccorsi R. & Zacny K.A. (2008). Design and practices for use of automated drilling and sample handling on MARTE while minimizing terrestrial and cross contamination. *Astrobiology* **8**, 947 - 955.

Murphy, A. & Paling, S. (2012). The Boulby Mine Underground Science Facility: The search for Dark Matter, and beyond. *Nuclear Physics News* **22**, 19-24.

- Ojha, L., Wilhelm, M.B., Murchie, S.L., McEwen, A.S., Wray, J.J., Hanley, J., Masse, M. & Chojnacki, M. (2015). Spectral evidence for hydrated salts in recurring slope lineae on Mars. *Nat. Geosci.* **8**, 829–832.
- Osterloo, M.M., Hamilton, V.E., Bandfield, J.L., Glotch, T.D., Baldrige, A.M., Christensen, P.R., Tornabene, L.L. & Anderson, F.S. (2008). Chloride-bearing materials in the southern highlands of Mars. *Science* **319**, 1651–1654.
- Osterloo, M.M., Anderson, F.S., Hamilton, V.E. & Hynek, B.M. (2010). Geologic context of proposed chloride-bearing materials on Mars. *J. Geophys. Res.* **115**, E10.
- Payler, S.J. *et al.* (2016). Planetary Science and Exploration in the Deep Subsurface: Results from the MINAR Program, Boulby Mine, UK. *Intern. Journ. Astrobiol.* **15**, 333-344.
- Picardi, G. *et al.* (2005). Radar soundings of the subsurface of Mars. *Science* **310**, 1925-1928.
- Platonov, A. (1979). Color of minerals. *Naukova Dumka, Kiev (in Russian)*.
- Poole, R.T., Liesegang, J., Leckey, R.C.G. & Jenkin, J. G. (1975). Electronic band structure of the alkali halides. II. Critical survey of theoretical calculations. *Physical Review B* **11**, 5190.
- Quick, J. *et al.* (2016). Real-time, portable genome sequencing for Ebola surveillance. *Nature* **530**, 228-232.

- Richter, L., Coste P., Gromov V., Hochan H., Pinna, S. & Richter, H-E. (2001). Development of the “planetary underground tool” subsurface soil sampler for the Mars express “Beagle 2” lander. *Advances in Space Research* **28**, 1225-1230.
- Saul, D.J., Aislabie, J.M., Brown, C.E., Harris, L. & Foght, J.M. (2005). Hydrocarbon contamination changes the bacterial diversity of soil from around Scott Base, Antarctica. *FEMS Microbiol. Ecol.* **53**, 141–155.
- Smith, N.J.T. (2012). The development of deep underground science facilities. *Nuclear Physics B - Proceedings Supplements* **229-232**, 333-341.
- Smith, H.D. & McKay, C.P. (2005). Drilling in ancient permafrost on Mars for evidence of a second genesis of life. *Planet Space Sci.* **53**, 1302-1308.
- Squyres, S.W. *et al.* (2004). In situ evidence for an ancient aqueous environment at Meridiani Planum, Mars. *Science* **306**, 1709–1714.
- Stein, N.T. *et al.* (2018). The formation and evolution of bright spots on Ceres. *Icarus* (in press).
- Vago, J.L., Westall, F., Coates, A.J., Jaumann, R., Korablev, O., Ciarletti, V., Mitrofanov, I., Josset, J.L., De Sanctis, M.C., Bibring, J.P. & Rull, F. (2017). Habitability on early Mars and the search for biosignatures with the ExoMars Rover. *Astrobiology* **17**, 471-510.
- Watters, T.R. *et al.* (2006). MARSIS radar sounder evidence of buried basins in the northern lowlands of Mars. *Nature* **444**, 905-908.

Whiticar, M.J. (1999). Carbon and hydrogen isotope systematics of bacterial formation and oxidation of methane. *Chemical Geology* **161**, 291-314.

Williams, K.E., McKay, C.P., Toon, O.B. & Head, J.W. (2010). Do ice caves exist on Mars? *Icarus* **209**, 358-368.

Woods PJE. (1979). The geology of Boulby Mine. *Economic Geology* **74**, 409-418.

Zorzano, M.-P., Mateo-Martí, E., Prieto-Ballesteros, O., Osuna, S., Renno, N. (2009). Stability of liquid saline water on present day Mars. *Geophys. Res. Letters* **36**, L20201.

Zorzano, M.-P., Martin-Torres, J., Mathanlal, T., Ramachandran, A.V., and Soria-Salinas, A. (2017). 23rd ESA Symposium on European Rocket and Balloon Programmes. Visby, Sweden. ESA Proceedings.

## **Figure legends**

**Fig. 1.** A. Surface image of Boulby Mine, B. Location of Boulby Mine, C. The inside of the Boulby Underground Laboratory, D. Schematic of the Boulby Underground Science Laboratory and Mars Yard.

**Fig. 2.** Sites where samples were acquired and studied during MINAR 5 in relation to the underground laboratory and mine roadways (top). The ‘Lab’ constitutes the underground laboratory and Mars Yard (see Fig. 1). Depths below sea level are shown. A. Polygons experimental area. The dark lineations of the polygons can be seen in the wall behind the

sampling team. B. Brine sampling experimental area. ESA astronaut Matthias Maurer samples brine solutions at the edge of the pool.

**Fig. 3.** A flow chart showing the sequence of sample analysis in MINAR 5 to emulate robotic or human exploration studies on other planetary surfaces.

**Fig. 4.** Some of the sample acquisition instrumentation deployed in MINAR 5. A-C NASA drill (A. The Hilti Drill TE 50, 1050 Watts; B. 42 cm Core String; 40.6 cm Cuttings String; 92.7 cm cuttings string; C. Core Drill Bit diameter 5 cm and 7 cm long, D. The SPLIT instrument in operation on an artificial outcrop of halite in the Mars Yard; E. The use of MINAR for the methodical development of the SPLIT technology (see ‘Results’ for details).

**Fig. 5.** Some of the analytical instrumentation deployed in MINAR 5. A. Close-Up Imager (CLUPI) (seen as the camera on the tripod, top left), B. UV Fluorescence spectrometer (showing schematic of instrument set-up on left and image of instrument on right), C. Raman spectrometer (showing schematic of instrument set-up on left and image of instrument on right), D. Minion DNA sequencer, E. ATP/LAL analysis (LAL lab-on-a-chip top left and bottom left, ATP luminometer on right), F. Metabolt.

**Fig. 6.** Some environmental analysis equipment deployed in MINAR 5. A. HABIT and Perpetual Environmental Station (PES), B. PACKMAN and PES.

**Fig. 7.** Drilling into Permian halite. A and B. Drilling into salt polygon boundary junction (darker coloured strip) using the NASA Mars IceBreaker drill and Core string.

**Fig. 8.** The Universal Planetary Sampling Bag. A. Diagrammatic concept of bag. B. A prototype bag. C-F. Sequence of images showing use of bag prototype. C. Bag is opened using perforated flanges that remain attached to bag. D. Internal flaps allow for grabbing motion within the bag to obtain sample. E. Sample is acquired and pulled into bag. F. Sample inside bag with flanges wrapped down to seal bag. One-way air valve (bottom left) used to remove excess air. G An example prototype bag that uses a glove attachment inside for sample grabbing (see text for discussion).

**Fig. 9.** CLUPI images of key evaporite materials in Boulby. A,B. halite, C. potash, D. polyhalite, E. Material at the edges of a NASA drill hole through polygon material, F. secondary NaCl mineralisation near the edges of a brine seep.

**Fig. 10.** UV fluorescence spectroscopy. A-C. Images of halite, potash and polyhalite obtained under 280 nm and 365 nm illumination, at room temperature. D. Spectra obtained of the three samples for a 365 illumination at room temperature.

**Fig. 11.** Raman spectroscopy. Spectral plots of A) halite, B) iron oxide/clay inclusions in potash, C) polyhalite.

**Fig. 12.** A. Concentration distribution of LPS. Error bars are the %CV for each duplicate assay. Samples are as follows: First nine samples are solid salt samples of polyhalite, halite and potash. Following three samples ('polyg 2-3') are samples from polygons in polygons experimental area. Following 19 samples are evaporite ('wht evap'), salt stalagmite ('stalag') and brine samples ('brine 2-3') from brine sampling experimental area. B. ATP in ancient and



modern evaporite/brine system using selected samples in (A) including a sample from the ground at the laboratory entrance (far right).

**Fig. 13.** Metabolt operation. A. Comparison of electrical conductivity in samples with and without glucose. B. Comparison of redox potential (Eh) in samples with and without glucose, C. Comparison of change in carbon dioxide levels in samples with and without glucose; (inset) anti-correlation with oxygen levels.

**Fig. 14.** Methane concentrations, sampled in the atmosphere within 13 locations in the Boulby Mine tunnels, plotted against their respective  $\delta^{13}\text{C-CH}_4$  values. The simplest explanation for the range of values is mixing between a thermogenic source and an atmospheric (ambient surface derived air) source. The value for the atmosphere endmember is taken from Whiticar (1999).

**Fig. 15.** Raw data of methane concentration ( $^{12}\text{C}$ ) within mine atmosphere samples (flat topped peaks) and gases extracted from the two potash samples (two highest peaks on right hand side of plot), as measured by the Picarro G2201-i cavity ring down spectrometer. No methane was detected within the other suites of mineral samples tested (halite, polyhalite).

**Fig. 16.** 3D mapping. A. Close range 3D mapping image done in the Boulby Mine with a rock sample. B. Long range 3D mapping of the wall of the mine shaft. The small box on the bottom right of the image is the PACKMAN instrument.

**Fig. 17.** PACKMAN operation. Figure showing the lower background radiation experienced in Boulby Mine (dots) compared to surface particle flux (solid line), validating the instrument in a ‘quiet’ radiation environment.